

FEATURES



- **Wireless Digital Transmission of Video and Audio**
- **Wireless Range Max. 120 meter (at the open space)**
- **Secured wireless link**
- **Free Input Voltage (DC 10V ~ 32V)**
- **Re-pairing function to enable interchanging trailers and trucks each other**
- **Adaptive Frequency Hopping (smart modulation)**
- **Display signal strength indicator**
- **Status LEDs (power & pairing)**
- **IP69K waterproof (transmitter & receiver)**
- **Anodized aluminum housing (corrosion-proof)**

Specifications

Operating frequency	2370MHZ ~ 2510MHZ Digital Wireless Rx/Tx
Modulation system	Adaptive Frequency Hopping
Wireless range	Max. 120 meter (at the open space)
Latency	Under 150 msec communication (at the open space)
TV system	PAL
Image Encoding	MPEG4
Video Input/Output	CVBS 1.0VP-P, 75Ω
Audio Input/Output	AUDIO Max. 2VP-P, 50Ω
High Resolution	720 x 576 (PAL)
Power supply	DC 10 ~ 32V
Power consumption	2.4 Watt Max.
Current consumption	200 mA Max. (at 12V DC)
Operating temperature	-30°C ~ 70°C
IP Rating	IP69K
Dimensions	Transmitter (TX): 100mm x 93mm x 25mm Receiver (RX): 100mm x 93mm x 25mm
Weight	Transmitter (TX): approx. 0,75 Kgs incl. cables Receiver (RX): approx. 0,75 Kgs incl. cables